



Smart 2430V3 Zero Client

Profile

Smart 2430 V3 is Zero client based on quad-core ARM Cortex A53 SOC(System on Chip) CPU and embedded Linux OS. It delivers deeply optimized RDP 10 (RemoteFX) client, and supports Windows 7/8/10, as well as Multipoint and Windows servers, etc.



Smart 2430V3 Zero Client

Features



HD Experience

Up to 1920*1080p 32bpp display, Video redirection, Supports remotefx vGPU virtualization with 3D experience.USS redirection, Video Redirection for SMB,Video Redirection forVDI.

Free VDCClass Software

VDCClass is an easy and simple e-class software, which could broadcast the teacher's desktop to all the Zero clients in LAN.

Desktop Broadcasting

SMART 2430 V3 is a Zero client integrated the receiver of DesktopCaster, which could receive the video stream from DesktopCaster. In most cases, the DesktopCaster software could be used to broadcast the teacher s Windows desktop directly to zero clients instead of the student's remote desktops.

Free Management Software

TCM(Zero Client Management System) is a free software to manage all the Smart 2430 V3 Zero client. It delivers many features to control the devices over network.

Connectivity



- 1 Power Button
- 2 Multimedia Ports
- 3 USB 2.0 Ports
- 4 Kensington Lock
- 5 USB 2.0 Ports

- 6 DC in
- 7 LAN Port
- 8 USB 2.0 Ports
- 9 HDMI Ports
- 10 VGA Port



Specification



Processor	Cortex A53 Quad-core 1.5 Ghz Soc(System on Chip
Protocol	RDP10
System Memory	1GB SOC
Storage	8GB eMMC
Display	Resolution Support up to 1920 X 1200 @ 60 Hz with 24/32 bit color
Supported OS	Windows 7/8/10, Linux OS Windows Multi Point Server 2008 R2/2012 R2/2016 R2, 2019
Multimedia Support	Hardware-accelerated 2D graphics, hardware-accelerated video support for most media formats on stand-alone media player applications and browser-based video
Output	1xVGA, 1xHDMI port, 5xUSB port, Input 1xDC port, 1xRJ45 port, 3.5mm stereo audio jacks for head hone & micro hone.
Network	10/100/1000 Base-T Fast Ethernet, RJ-45
Size	107 X 107 X 28mm
Weight	0.25KG
Rated output current (max)	3A
Output voltage	+5V DC
Operating temperature	0° ~ 35°
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60Hz
Cooling	Fan-less Convection





Zero Client

Smart 2430V3

Contact

SURENDRANAGAR

2nd Floor, Manivir Complex,
Vitthal Press Road, Surendranagar.
Pin 363001.
Gujarat, INDIA.
Cell. : +91 982 420 8213
+91 937 465 1621,
E-mail : sales@smartstation.in

AHMEDABAD

Apurva Computers Technologies Pvt Ltd
1210, 12th Floor, One World West,
Bopal Approach BRTS Bus stop,
Near Vakil Saheb Bridge, Bopal,
Ahmedabad - 380058
Cell. : +91 982 420 8213
+91 937 465 1621,
E-mail : sales@smartstation.in

