

DCS-F5714-L1

4MP Fixed Bullet Network Camera



KEY FEATURES

- 1/2.7" Progressive scan CMOS Sensor
- 3.6mm Fixed lens
- Up to 2560 x 1440 Full HD resolution
- IR Range up to 30 Mtr.
- DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC
- Support Defog, ROI, BLC, HLC UPnP-TM
- Support smart functions
- Support dual stream

SPECIFICATION

CAMERA

Image Sensor	1/2.7" Progressive scan CMOS Progressive
Min. Illumination	0.01lux (Color), 0lux (IR on)
Shutter Time	Auto/Manual, 1/3~1/10000s
Lens	3.6 mm@F2.0: horizontal FOV: 86°, vertical FOV:64.5°
Lens Mount	M12
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	DWDR
Max. IR LEDs Length	30M
Smart IR	Support

COMPRESSION STANDARD

Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps ~ 8Mbps

IMAGE

Max. resolution	4MP (2560×1440)
Main Stream	50Hz: 20fps 4MP(2560 × 1440), 25fps 3MP(2048 × 1536), 25fps 1080P(1920 × 1080), 25fps 960P(1280 × 960) 60Hz: 20fps 4MP(2560 × 1440), 30fps 3MP(2048 × 1536), 30fps 1080P(1920 × 1080), 30fps 960P(1280 × 960)
Sub Stream	50Hz: 25fps D1(704 × 576),25fps CIF (352 × 288) 60Hz: 30fps D1(704 × 480),30fps CIF(352 × 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
HLC	50Hz:25fps CIF (352 × 288) 60Hz:30fps CIF (352 × 240)
BLC	Support
ROI	On/Off, zone configurable
Defog	Support

NETWORK

Event	Motion Detection, Video Shelter
Smart Functions	Area Intrusion, Line crossing
Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P, Bonjour,IPV6
System compatibility	Onvif 2.6, Profile S, CGI
Security	User authentication, IP address filtering, Video mask
Mobile Surveillance	iPhone, iPad, Android devices

INTERFACE	
Communication interface	1 RJ45 10M / 100M Ethernet Port
GENERAL	
Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%)
POE Supply	PoE (802.3af)
Power Consumption	Max. 7W
Weather Proof	IP66
Dimensions	187*64*64mm
Weight (without HDD)	300g
Certification	CE
SYSTEM MANAGEMENT	
Mobile Software	D-Link Smart CCTV App
Desktop Software	DSVS (D-Link Smart Video Surveillance)
System Requirement for Web Interface	IE