eSSL®

Security at Fingertips

Canteen Management System

LP400

Specification

Templates : 3000

Transactions : 1,00,000

CPU : 32bit Microprocessor 400MHz

Memory : 32M RAM, 256M Flash

Communication Port : Ethernet , USB-host, WiFi (Optional)

Fingerprint Sensor : Optical Sensor

Algorithm : Finger 10.0

Verification time : <=1 sec

FRR : <=1%

FAR : <=0.0001%

Printer : Thermal

LCD : 3 inch TFT Screen

LED Indicator : Red and Green

Power : 12V DC, 3A

Operating Temperature : 0ºC - 42ºC

Operating Humidity : 20% - 80%

Dimension (LxWxD) : 171 x 284 x 120 mm

Weight : 2.2 kg

Features

-- Built-in thermal printer

-- Color TFT Screen with GUI interface for easy use

-- One second user recognition

-- Stores 3000 templates and 1,00,000 transactions

-- Reads fingerprint and/or PINs

-- Optional integrated proximity or smart card reader

-- Built-in serial and Ethernet ports

-- Built-in USB port allows for manual data transfer when network isn't available

-- Built-in bell scheduling

-- Audio-visual indicators for acceptance and rejection of valid/invalid fingers

-- Device as Inbuilt PUSH DATA Feature and Supports Web Application Software

---

www.esslsecurity.com

ISO FC C€ RoHS