




Smart Talky

	Squelch noise	
High power		Scan
	Low power	
CH with CTCSS		CH with DCS



Smart Talky

- LED display
- 99 Channels
- Very Long Range
- High Capacity Battery
- Menu Display Mode
- Low battery strength display
- Channel Number/Name display



Smart Talky

General specification

Name	Smart Talky Device
Model	Smart Talky
Frequency	UHF
Channel capacity	99
Frequency band	350-390 MHz
Weight	220 gms with Battery
Dimension	100 X 57 X 35 mm
Rated voltage	DC: 7.4V
Temperature range	-20°C ~ ±60°C
Battery Capacity	2000 mAh Battery (BIS Approved)
Battery Type	Li-ion Battery
Rx Sensitivity	0.18uV
Selectivity	≥ 60dB
Audio Power	≥1W
Modulation Emission	11KOF3E (12.5KHz)
Frequency Stability	± 1.5 PPM
Tx Power Output	1 - 4 W
Water Resistant	<Meets IP55 Standards
Rugged Construction	Meets MIL STD 810

- **VOX (Voice Operated Transmission)**
- **107 PL (Private Lines Codes)**
- **56 DPL (Digital Private Lines codes)**
- **Channels Scan with Call back**
- **Priority Scan with Call Back**
- **Time Out Timer with Pre Alert**
- **Voice Annunciation**
- **Busy Channel Lock Out**
- **Multiple Call Tones**
- **Call Alert Tone in Group**
- **Emergency Alert in Group**
- **Low Battery Alert**
- **Automatic/Manual Key Lock**
- **Auto Wakeup LED Display**
- **Battery Voltage Display**
- **Call Strength Indicator**
- **Battery Saver Circuit**

** Note: All Stated Specification are subject to change in our endeavour of continuous improvement.*

Standard and Optional Accessories:



AC Adaptor



Li-ion Battery Pack



Rapid Charger



Earpiece (Optional)



Belt Clip



Handstrap